SAFETY DATA SHEET

ACCORDING TO THE INSTRUCTIONS OF 2001/58/EK

PRODUCT: MAGNET CHROM

EDITION: 1.00

REVIEW DATE: 10/9/2012

1. PREPAIRATION/COMPANY DETAILS

1.1 PREPAIRATION DETAILS

MAGNET CHROM-MAGNETIC BLACKBOARD

1.2 PRAPAIRATION USE

MINERAL WATER SUBSTRATE FOR INTERIOR COATINGS

1.3 COMPANY DETAILS

MANUFACTURER: EVOMAT

LOCATION: KORINTHOU 4 ELEFSIS

E-MAIL: <u>contact@evomat.com</u>

Website: www.evomat.com

Tel. number: 2105545078, 2105565470

Emergency phone: 2107793777

2. PRODUCT INGREDIENTS

DANGEROUS COMPONENTS	CAS NUMBER	DANGER SYMBOLS	PHRASES R	% PROPORTION(CUBIC)
-	-	-	-	-

3. SPECIFICATIONS

CLASSIFICATION: NOT CLASSIFIED AS DANGEROUS ACCORDING TO 2001/58/EK		
-		
HEALTH DANGER:	-	
SAFETY DANGER:	-	
ENVIRONMENTAL DANGER:	-	

4. FIRST AID

page 1

	-
AFTER INHALATION	MOVE OUTSIDE IN FRESH AIR. IN CASE OF VERTIGO OR
	SENSES WEAKNESS, SEEK FOR MEDICAL ATTENTION.
IN TOUCH WITH SKIN	RINSE WITH WATER AND SOAP
IN TOUCH WITH EYES	IN CASE OF IRRITATION, SEEK FOR MEDICAL ATTENTION
AFTER SWALLOWING	DO NOT VOMIT. SEEK FOR MEDICAL ATTENTION AND
	SHOW THE SAFETY DATA SHEET.

5. FIRE FIGHTING MODES

SPECIAL DANGERS	-
EXTINGUISHING	THE PRODUCT IS NOT FLAMMABLE
PROTECTIVE EQUIPMENT	COMPLETED PROTECTIVE CLOTHING AND INDEPENDENT
	RESPIRATORY DEVICE

6. TREATMENT OF ACCIDENTAL RELEASES

PRECAUTIONS	AVOID TOUCHING THE PRODUCT. USE SUITABLE GLOVES (PVA), PROTECTIVE GLASSES AND CLOTHING. IF THE LEAK WILL BE DONE IN CLOSED AREA, YOU HAVE TO VENTILATE.
ENVIRONMENT PRECAUTIONS	STOP THE LEAK, IF IT IS POSSIBLE. PREVENT THE WIDE DISPRERSION ON GROUND AND THE WATER ENVIRONMENT. USE SAND, SOIL OR ABSORBENTS TO LIMIT THE LEAK
CLEANING METHODS	COLLECT AS MUCH MATERIAL AS POSSIBLE IN A SUITABLE POT FOR REJECTION. HOLD THE PAINT USINGAGGREGATES US SAND, SOIL etc. IN CONTINUOUS, REMOVE THAT, IN SUITABLE POT ACCORDING THE LEGISLATION.

7. OPERATION AND STORAGE

	WORKING ALWAYS IN FRESH AIR AREA, DIFFERNTLY USE
	A SUITABLE FACE MASK. DO DOT EAT OR DRINK WHILE
OPERATION	WORKING. AVOID TOUCHING WITH SKIN AND EYES. DO
	NOT INHALE THE VAPOR. USE THE PRODUCT IN
	TEMPERATURES FROM 5 TO 40 ⁰ C.
	KEEP THE POTS AWAY FROM KIDS.DO NOT STORAGE THE
STORAGE	PRODUCT IN TEMPERATURE UP TO 50 ⁰ C. PROTECT
	FROM FROST.

8. PHYSICAL AND CHEMICAL PROPERTIES

VIEW	VISCOUS LIQUID
COLOUR	BLACK
ODOR	CHARACTERISTIC
BOILING POINT	~100 [°] C (WATER)
MELTING POINT	NOT IDENTIFIED
РН	8.5 - 9
FLASH POINT	NOT APPLICABLE
SPONTANEOUS COMBUSTION TEMPERATURE	NOT APPLICABLE
EXPLOSIVE PROPERTIES	NO
OXIDIZING PROPERTIES	NO
SOLUBILITY IN WATER	UNLIMITED ON 20 ⁰ C
VAPOR DENTITY	NOT IDENTIFIED
SATURATED STEAM (25 [°] C)	-
STEAM VOLTAGE (20 ⁰ C)	20 h Pa 20 ⁰ C
STEAM VOLTAGE (50 [°] C)	-
SPECIAL WEIGHT	2.3 – 2.5 KG/LT 250 C
VISCOSITY	14000-20000 CPOISE 23 ⁰ C

9. STABILITY AND ACTIVITY

STABILITY	THE PRODUCT IS STABLE IF THE STORAGE AND USING
	BECOME ACCORDING THE INSTRUCTIONS
CONDITIONS WHICH YOU HAVE TO AVOID	TEMPERATURES BETWEEN 5 [°] C AND 40 [°] C
MATERIALS WHICH YOU HAVE TO AVOID	STRONG ACIDS, BASES, OXIDANTS & REDUCING AGENTS
DETERIORATION MATERIALS	NO DECOMPOSITION IN DANGEROUS PRODUCTS

10. TOXICOLOGICAL INFORMATION

DETAILED TOXICOLOGICAL INFORMATION ARE NOT AVAILABLE, BECAUSE THE PRODUCT DOES NOT HAVE SUBMITTED THE TOXICOLOGICAL TEST. ACCORDING TO OUR EXPERIENCE, DO NOT HAVE MANIFESTED DANGERS ON USERS HEALTH, WHEN USED RIGHT. POSSIBLE INDICATIONS RECORDED BELOW:

POSSIBLE INDICATIONS	IRRITATION OF SKIN, EYES AND RESPIRATORY SYSTEM. HEADACHE,
	VERTIGO, NAUSEA, LOSS OF SENSES
-IN TOUCH WITH EYES	MAY CAUSE LIGHT IRRITATION
-IN TOUCH WITH SKIN	REPEATED EXPOSURE CAN CAUSE DERMATITIS AND IRRITATION
-SWALLOWING	EXPOSURE ON ENVIRONMENT WITH HIGH VAPOR CONCENTRATION
	CAN CAUSE NOSE, THROAT AND BREATH IRRITATION
-INHALATION	-

11. ECOLOGY INFORMATION

THE PRODUCT HAS NOT SUBMITTED IN A SIMILAR TEST, SO DETAILED INFORMATION ABOUT ENVIRONMENT TOXICOLOGY IS NOT AVAILABLE. CAUSE OF ITS COMPONENTS CAN BE CAUSED PROBLEMS TO FACILITIES OF BIOLOGICAL WASTE CLEANING. FOR THAT REASON, AVOID DTHROW THE PRODUCT INTO DRAINS AND AQUATIC ENVIRONMENT.

12. TRANSPORT INFORMATION

ROAD TRANSOPRT (ADR/RID)

UN NUMBER	THERE IS NO LIMIT
MISSION NAME	
SPECIAL ORDINANCE 640	
KIND NUMBER	
CLASS(ADR/RID)	
PACK GROUP	

SEA TRANSOPRT (IMDG)

UN NUMBER	THERE IS NO LIMIT
MISSION NAME	
CLASS (IMDG)	
PACK GROUP	
SEA POLLUTION	

AIR TRANSORT (ICAO/IATA)

UN NUMBER	THERE IS NO LIMIT
MISSION NAME	
CLASS (ICAO/IATA)	
PACK GROUP	

13. INFORMATION ABOUT REGULATORY

CLASSIFIED	-	
SYMBOLS	-	
DANGER FRASES (R)	-	-
SAFETY FRASES (S)	1/2	BE LOCKED OUT AND AWAY FROM
		KIDS
	24/5	AVOID TOUCH WITH SKIN AND EYES
	28	IN CASE OF TOUCH WITH SKIN,
		WASH IMMEDIATELY WITH PLENTY
		OF WATER AND SOAP.
	29	DO NOT THROW THE CONTENT IN
		DRAINS
ANOTHER FRASES		-

14. ANOTHER INFORMATION

THE PRODUCT IS SUITABLE FOR USE FROM PUBLIC. THE SAFETY DATA SHEET IS ACCORDING TO 91/155/EOK AND ITS MODIFICATION.

THE INCLUDED INFORMATION IN THIS SAFETY DATA SHEET, RESULTING FROM OUR EXPERIENCE AND OUR KNOWLEDGE, UNTIL THE EDDITION DATE AND IS AIMED TO UPDATE THE PRODUCT USER IN ISSUES OF SAFE PROCESSING, STORAGE, TRANSPORTATION AND AVAILABILITY. IT IS NOT QUARANTEE OR QUALITY SPECIFICATION. THE INFORMATION RELATED ONLY WITH THE PARTICULAR MATERIAL WHICH IS DESCRIBED AND IS NOT APPLICABLE IN COMBINATION WITH OTHER MATERIALS OR ANOTHER PROCESS.

